

# INSULFLEX®

## Technical Data Sheet

### PyroRope™

Product Name: PyroRope™

Technical Description: Braided E-Glass rope with a thick covering of iron oxide red silicone rubber.

Temperature Capabilities: Rated for 500°F (260°C) continuous exposure, up to 2000°F (1093°C) for 15-20 minutes, and up to 3000°F (1650°C) for 15-30 seconds.

Product Overview: PyroRope is an ideal high temperature gasket where extra abrasion resistance and or the ability to withstand oil, moisture, molten splash, or flame is required.

PyroRope also offers excellent resistance to corrosive atmosphere, moisture, chemicals, vibration, and electricity.

Dimensional Data: A variety of braided ropes can be used as the substrate to achieve the desired compression density.

Diameters available from 1/4" (6 mm) to 1-1/4" (32mm)

Installation: To achieve proper seal, rope densities may vary for each application.

Cautionary Notes: N/A



Disclaimer: Due to the range of possible applications, no warranty is expressed or implied. ADL Insulflex, Inc.'s liability is limited solely to the replacement of defective material. ADL Insulflex, Inc. will not be held liable for any consequential damages arising from the use or misuse of the material. While the information given herein is believed to be reliable, ADL Insulflex, Inc. makes no warranties as to the accuracy or completeness. Samples of all Insulflex® products are available at no cost or obligation, and suitable trials should be made prior to installation.

**Telephone**  
**North America: 800 461 9323**  
**International: 905 377 1461**

**ADL Insulflex, Inc.**  
**8783 Dale Road**  
**Cobourg, Ontario**  
**K9A 4J9**  
**Canada**

**Fax**  
**North America: 800 461 9328**  
**International: 905 377 1484**