

Fiberflect™ Tape AB

Product Name: Fiberflect™ Tape AB

Technical Description: A highly reflective, high adhesion tape ideal for radiant heat applications. Fiberflect™ Tape AB is constructed of a texturized glass fiber base. One side consists of a thin layer of aluminum foil and the other, a pressure sensitive adhesive to facilitate installation.



The durable construction of Fiberflect™ Tape AB is suitable for demanding applications up to 400°F (204°C) continuous operating temperature. The glass base fabric will stay intact up to 1000°F (538°C)

Product Overview: Fiberflect™ Tape AB has good flame, abrasion, water and oil resistance characteristics, and exhibits outstanding properties of flexibility, toughness, and tensile strength.

Fiberflect™ Tape AB is designed to reflect radiant heat energy, minimizing the heat energy transfer through the glass fiber base.

Fiberflect™ Tape AB has a thickness of 0.027" (.76mm) and is available in 2" (51mm) and 4" (102mm) widths in 150ft rolls.

Installation: Depends on a wide variety of application parameters.

Cautionary Notes: Not recommended for extreme molten splash applications.

Disclaimer: Due to the range of possible applications, no warranty is expressed or implied. ADL Insulflex, Inc.'s liability is limited solely to the replacement of defective material. ADL Insulflex, Inc. will not be held liable for any consequential damages arising from the use or misuse of the material. While the information given herein is believed to be reliable, ADL Insulflex, Inc. makes no warranties as to the accuracy or completeness. Samples of all Insulflex® products are available at no cost or obligation, and suitable trials should be made prior to installation.

Telephone
North America: 800 461 9323
International: 905 377 1461

ADL Insulflex, Inc.
8783 Dale Road
Cobourg, Ontario
K9A 4J9
Canada

Fax
North America: 800 461 9328
International: 905 377 1484