

# HAZARD COMMUNICATION SAFETY DATA SHEET

Doc: 2016-07-01.001

#### 1. Identification

Product Name: Cool Blue™ Aerostyle Pyrojacket®

Synonyms or Product Family: Firesleeve, Pyrosleeve

CAS Number: Continuous Filament E Glass Fiber – 65997-17-3
Silicone Rubber – Not Available-Proprietary Mixture

Recommended use: Protection of hoses and cables from heat and flame

Restriction on use: None known

Manufacturer/ Supplier: ADL Insulflex, Inc.

A member of the ADL Group.
Address: 8783 Dale Road

8783 Dale Road Cobourg, Ontario

Canada K9A 4J9
Telephone: (905) 377-1488
(800) 461-9323

Fax: (905) 377-1484 (800) 461-9328

### 2. Hazards Identification

OSHA/HCS status: While this material is not considered hazardous by the OSHA

Hazard Communication Standard (29 CFR 1910.1200), this

SDS contains valuable information critical to the safe

handling and proper use of the product. This SDS should be retained and available for employees and other users of this

product.

Classification of the substance or mixture: Not classified

**GHS Label Elements:** 

Signal Word No signal word

Hazard statements No known significant effects or critical hazards.

Precautionary statements:

Prevention Not Applicable
Response Not Applicable
Storage Not Applicable
Disposal Not Applicable

Supplemental label elements Emits toxic fumes when heated.

Hazards not otherwise classified None Known

# 3. Composition / Information on Ingredients

Component	CAS Number	Weight %
Continuous Filament E Glass <sup>1</sup>	65997-17-3	~50%
Silicone Rubber	Not available – Proprietary Mixture	~50%

Note: \*1 – As manufactured continuous filament glass fibers are not respirable. Continuous filament glass products that are chopped, crushed or severely mechanically processed during manufacturing or use may

contain a very small amount of respirable particulate, some of which may be glass shards. See section 8 of Safety Data Sheet for exposure limit data.

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: glass wool fiber, fibrous glass and nuisance particulates.

No additional information available.

Component Information/Information on Non-Hazardous Components

#### 4. First Aid Measures

Primary Route of Exposure:

Inhalation

Skin Contact

**Eye Contact** 

Description of necessary first aid measures:

Eye:

Skin: Inhalation: Ingestion: Inhalation, skin, eye

Dust and fibers from this product may cause mechanical

irritation of the nose, throat and respiratory tract.

Dust and fibers from this product may cause temporary

mechanical irritation to the skin.

Dust and fibers from this product may cause temporary

mechanical irritation to the eyes.

Flush for 15 minutes with copious amounts of lukewarm water. Seek medical attention if irritation persists. Wash thoroughly with warm water and non-abrasive soap. Remove person to fresh air and seek medical attention. Ingestion is unlikely. If it does occur, watch for several days to make sure intestinal blockage does not occur. If there is

blockage, seek medical attention.

# 5. Fire Fighting Measures

Suitable Extinguishing Media: Fire Fighting Procedures:

Unusual Fire and Explosion Hazards: Hazardous thermal decomposition products: Water spray; carbon dioxide; dry chemical; foam.

In a sustained fire, use self-contained breathing apparatus. None Known

Fiberglass will not burn, but smoking of the product may occur at approximately 400-500 °F (approximately 200-260 °C) due to decomposition of the surface binder. Surface binders may decompose in a fire situation and release carbon monoxide, carbon dioxide and water. Additionally, there are many chemicals that can evolve during any partial decomposition of chemical products. The amounts or

identities cannot be predicted and can differ in each situation. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any persona; risk without suitable training. Fiberglass itself will not support combustion, but in a sustained fire, proper protection against products of combustion from the fuel and sizing/binder must be worn.

Special Protective Equipment and Precautions for Fire Fighters:

## 6. Accidental Release Measures

Material is a solid. Vacuum or wet-sweep fibrous dust.

### 7. Handling and Storage

Precautions for handling and storage: Normal warehouse conditions.

#### 8. Exposure Controls / Personal Protection

#### **Exposure Limits:**

Component Name (CAS #)	OSHA PEL (8hr TWA)	ACGIH TLV (8hr TWA)
Continuous Filament E Glass (65997-17-3)	mg/m3	mg/m3
Non-respirable fibers and particulate	15 mg/m³ (total dust)(a)	5 mg/m³ (inhalable fraction)
Respirable particulate	5 mg/m³ (respirable dust)(b)	3 mg/m³ (PNCO)*
Respirable particulate with fiber like dimensions (glass shards)	None Established	1 fiber/cm³ aspect ratio >5:1
Silicone Rubber	Not Applicable	Not Applicable

<sup>\*</sup>PNOC = Particles not otherwise classified

Engineering controls: None known

Personal Protective Equipment (PPE): Loose fitting long sleeved shirt that covers to the base of the

neck, long pants and gloves. Skin irritation is known to occur chiefly at pressure points such as around the neck, wrist,

waist and between fingers.

Eye and Skin protection: Safety glasses with side shields or chemical splash goggles

must be worn to prevent eye contact. A good safety practice is to have an eye wash station readily available near the work

area.

Respiratory protection: Some applications of these products may not require

respiratory protection for fiberglass. However, if airborne fibrous glass concentrations exceed the OSHA permissible limits or if irritation occurs, a properly fitted NIOSH/MSHA approved disposable dust respirator such as the 3M model 8210 (formerly 8710) or model 9900 (in high humidity environments) or equivalent should be used. Use respiratory protection in accordance with your local regulations and

OSHA regulations under CFR 1910.134.

Ventilation: Local exhaust ventilation (if needed) to maintain appropriate

Not Applicable

airborne dust levels.

#### 9. Physical and Chemical Properties

Viscosity:

Physical State: Solid

Colour: White or off-white coloured interior with Blue exterior

Odour: None

Not Applicable Ordour Threshold: Not Applicable pH-value: Melting Point: Not Applicable Freezing Point: Not Applicable Not Applicable Initial Boiling Point/ Boiling Range: Flash Point: Not Applicable Not Applicable **Evaporation Rate:** Not Applicable Not Applicable

Flammability (Solid, Gas): **Explosion Limits:** Vapour Pressure: Not Applicable Vapour Density: Not Applicable Relative Density: Not Applicable Insoluble Solubility: Partition Coefficient: Not Applicable **Auto-Ignition Temperature:** Not Applicable Not Applicable **Decomposition Temperature:** 

# 10. Stability and Reactivity

Reactivity: Not Applicable

Chemical Stability: This is a stable material.

Possibility of Hazardous Reactions:

Conditions to Avoid:

Incompatible Materials:

None Known

None Known

Hazardous Decomposition Products: Sizings or binders may decompose in a fire. See Section 5 of

SDS for information on hazardous combustion products.

### 11. Toxicological Information

Signs and Symptoms of Overexposure: Material is considered inert.

Acute Effects:See Section 4Eye Contact:See Section 4Skin Contact:See Section 4Inhalation:See Section 4Ingestion:See Section 4

Chronic Effects and Carcinogenicity:

Silicone Rubber

E-Glass Fiber

**General Product Information** 

Carcinogenicity
Fiber Glass Continuous Filament

Inert substance with no known chronic effects or carcinogenicity.

Dusts may cause mechanical irritation of the eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. People with preexisting respiratory conditions, may experience difficulty breathing, congestion and chest tightness.

The International Agency for Research on Cancer (IARC) in June, 1987, categorized fiber glass continuous filament as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify fiber glass continuous filament as a possible, probable, or confirmed cancer causing material.

The American Conference of Governmental Industrial Hygienists (ACGIH) A4 classification, not classifiable as human carcinogen, for respirable continuous filament glass fibers is based on inadequate data in terms of its carcinogenicity in humans and/or animals.

For respirable continuous filament glass fibers, a TLV-TWA of 1 fiber/cc was adopted to protect workers against mechanical irritation. The TLV-TWA of 5 mg/m3 was adopted for nonrespirable glass filament fiber, measured as inhalable dust, to prevent mechanical irritation of the upper respiratory tract.

Note: There are no known chronic health effects connected with long-term use or contact with these products.

Products that are chopped, crushed or severely mechanically processed during manufacture or use may contain a very small amount of respirable glass fiber-like fragments. NIOSH defines "respirable fibers" as greater than 5 microns in length and less than 3 microns in diameter with an aspect ration of  $\geq$  5:1 (length-to-width ratio).

### Page 5 of 5

Ingestion Ingestion of this product is unlikely. May produce

gastrointestinal irritation and discomfort.

Medical Conditions Aggravated by Exposure: Chronic respiratory and skin conditions may temporarily

worsen from exposure to this product.

Acute Toxicity Values: None Known

### 12. Ecological Information

No data available for this product.

### 13. Disposal Considerations

Disposal method: Fiberglass and polymerized silicone rubber are generally

considered to be inert materials. No special disposal procedures need be followed. User should follow normal methods of disposal in accordance with any governmental

regulations.

## 14. Transport Information

UN Number:
UN Proper Shipping Name:
None
Transport Hazard Class(es):
None
Packing Group:
None
Environmental Hazards:
None
Transport in Bulk, if Applicable:
Special Precautions:
None

### 15. Regulatory Information

Safety, health and environmental regulations specific to the product:

WHMIS Hazard Class: Not known Harmonized Code: 8546.10.00.90

## 16. Other

Users are advised to ensure that this information is brought to the attention of their employees handling the product. The information given herein is believed to be reliable. However, ADL Insulflex, Inc. makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. ADL Insulflex, Inc.'s obligations shall be only as set forth in ADL Insulflex, Inc.'s standard terms and conditions of sale for this product. In no case will ADL Insulflex, Inc. be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product.

Users of ADL Insulflex, Inc. products should make their own evaluation to determine the suitability of each such product for the specific application and to establish safe handling and installation procedures.

SDS preparation date: July 1, 2016